


FOR P/N:
LMX73X021X2E
LMX73X021X2EJ
LMX73X021X2DE
LMX73X021X2EG

PinNo.	Symbol	Level	Function
1	V _{SS}	-	0V
2	V _{DD}	-	+5V
3	V ₀	-	-
4	RS	H/L	INSTRUCTION CODE INPUT REDATA INPUT
5	R/W	H/L	IN DATA READ (FROM LOW TO MPU) LD DATA WRITE (FROM MPU TO LOW)
6	E	H, H->L	ENABLE SIGNAL
7	DB0	H/L	DATA BUS LINE
8	DB1	H/L	
9	DB2	H/L	
10	DB3	H/L	
11	DB4	H/L	
12	DB5	H/L	
13	DB6	H/L	
14	DB7	H/L	
15	A	-	POWER SUPPLY FOR LED/EL
16	K	-	



NOTES :

- Resolution : 16X2 Characters
- Character Format : 5X8 Dots
- General Tolerance : ±0.5 mm

產品編號	LM_73_021_2E	南亞塑膠工業股份有限公司 NAN YA PLASTICS CORPORATION		
APPROVE	NAME	DATE	TITLE	製品圖
CHECK			DWG-NO	MXCX021XA Rev.A
DESIGN			THIRD ANGLE PROJECT	UNIT : mm
DRAW	MAY PING	86.11.07	SCALE :	