


No	Symbol	Function
1	VSS	GND,OV
2	VDD	+5V
3	VO	for LCD Drive
4	RS	Function Select
5	R/W	Read/Write
6	E	Enable Signal
7	DB0	Data Bus Line
8	DB1	
9	DB2	
10	DB3	
11	DB4	
12	DB5	
13	DB6	
14	DB7	
15	A	+5V
16	K	+0V



Note :

- 1.Resolution : 16X2 Characters
- 2.Character Format : 5X8 Dots
- 3.General Tolerance : ±0.5mm.
- 4.Resistance of E1 & E2

Product No.	E1	E2
LMX84X019X2E	0Ω	0Ω
LMX84X019X2DE	0Ω	0Ω
LMX84X019X4E	0Ω	0Ω
LMX84X019X7DE	1MΩ	0Ω
LMX84X019X8X	0Ω	0Ω
LMX84X019X9X	0Ω	0Ω

PS. E1: Between BEZEL & GND of PCB.
E2: Between Mounting Hole & GND of PCB.

P/N :

- LMX84X019X2E
- LMX84X019X2DE
- LMX84X019X4E
- LMX84X019X7DE
- LMX84X019X8X
- LMX84X019X9X

產品編號	LM_84_019__E	南亞塑膠工業股份有限公司 NAN YA PLASTICS CORPORATION		
APPROVE	NAME	DATE	TITLE	製品圖
CHECK			DWG-NO	MXFX019XA Rev.A
DESIGN			UNIT	: mm
DRAW	MAY PING	87.07.01	THIRD ANGLE PROJECT	SCALE :