


PinNo.	Symbol	Level	Function
1	V _{SS}	—	0V
2	V _{DD}	—	+5V
3	V ₀	—	—
4	RS	H/L	H:INSTRUCTION CODE INPUT L:DATA INPUT
5	R/W	H/L	H:DATA READ (FROM LCM TO MPU) L:DATA WRITE (FROM MPU TO LCM)
6	E	H,H->L	ENABLE SIGNAL
7	DB0	H/L	DATA BUS LINE
8	DB1	H/L	
9	DB2	H/L	
10	DB3	H/L	
11	DB4	H/L	
12	DB5	H/L	
13	DB6	H/L	
14	DB7	H/L	



Note :

- 1.Resolution : 24 Characters x 2 Lines
- 2.Character Format : 5 x 8 Dots
- 3.Controller : KS0066 (Compatible)
- 4.DC/DC Converter : Without
- 5.General Tolerance : ±0.5 mm

產品編號	LM_B3_025_2	南亞塑膠工業股份有限公司 NAN YA PLASTICS CORPORATION		
APPROVE	NAME	DATE	TITLE	製品圖
CHECK			DWG-NO	Mx-x025x2 Rev.A
DESIGN			UNIT : mm	
DRAW	May Ping	87.03.24	THIRD ANGLE PROJECT	SCALE :