



3.GENERAL TOLERANCE : ±0.5mm

Pin No.	Symbol	Description	
1	VSS	Power Supply (GND)	
2	VDD	Power Supply	
3	VO	LCD Driving Voltage	
4	VOUT	Power Supply (-5V)	
5	A0	Control/Data Selection	
6	E1	Chip Enable for IC1	
7	E2	Chip Enable for IC2	
8	DB0	Data Bus	
9	DB1		
10	(RES)		Reset Control Signal
11	NC		Non-Connection
12	DB2		
13	DB3		
14	DB4		
15	DB5	Data Bus	
16	DB6		
17	DB7		
18	NC	Non-Connection	
19	(EL1)	EL Backlight Connection	
20	(EL2)		

NOTES:

- 1.RESOLUTION : 122X32 Dots
- 2.DOT SIZE : 0.38mmX0.38mm
DOT PITCH : 0.43mmX0.43mm
- 3.GENERAL TOLERANCE : ±0.5mm
- 4.CONTROLLER: SED1520

產品編號	LMA63_036_M	南亞塑膠工業股份有限公司 NAN YA PLASTICS CORPORATION		
APPROVE	NAME	DATE	TITLE	製品圖
CHECK			DWG-NO	MA-X036XM Rev.A
DESIGN				UNIT : mm
DRAWN	MAY PING	86.11.07		SCALE : 2/3