


PinNo.	Symbol	Level	Function
1	VSS	-	GROUND
2	VDD	-	POWER SUPPLY FOR LOGIC CIRCUIT
3	VEE	-	POWER SUPPLY FOR LED
4	A ϕ	H/L	L-INSTRUCTION H-DATA
5	CS1	L	CHIP ENABLE ACTIVE "L"
6	CS2	L	CHIP ENABLE ACTIVE "L"
7	CL	H/L	EXTERNAL CLOCK(20KHZ)
8	RD(E)	-	RD FOR 80 SERIE FOR 68 SERI
9	WR(R/W)	-	WR FOR 80 SERIA/W FOR 68 SERI
10	DB0	H/L	DATA BUS LINE
11	DB1	H/L	
12	DB2	H/L	
13	DB3	H/L	
14	DB4	H/L	
15	DB5	H/L	
16	DB6	H/L	
17	DB7	H/L	
18	RES	H/L	L=80 SERIEL H=68 SERIEL
19	VLED+	-	POWER SUPPLY FOR LED BACK LIGHT
20	VLED-	-	



Note :
1.Resolution : 122X32 Dots

產品編號	LM_84_042_	南亞塑膠工業股份有限公司 NAN YA PLASTICS CORPORATION		
APPROVE	NAME	DATE	TITLE	製品圖
CHECK			DWG-NO	MXAX042X Rev.A
DESIGN			UNIT	mm
DRAW	MAY PING	86.11.6	SCALE	1/1