



NOTE :

1. RESOLUTION : 320 X 3(R.G.B.) X 240 DOTS
2. CONTROLLER : WITHOUT
3. DC/DC CONVERTER : WITHOUT
4.
 - ① INTERFACE CONNECTOR
FFC, N16 P1.0mm
 - ② CCFT CONNECTOR
M63M83-04(MITSUMI)
5. TOLERANCE NO SPECIFIED : ±0.5mm

PIN ASSIGNMENT OF I/O CONNECTION

Pin No.	SYMBOL	LEVEL	FUNCTION
1	FLM	H/L	First Line Marker
2	LP	H-L	Data Latch Signal
3	CP	H-L	Data Shift Clock Signal
4	DISPOFF	H/L	H : Display On L : Display Off
5	V _{DD}	-	Power Supply for Logic
6	V _{SS}	-	Power Supply(OV,GND)
7	V _{LD}	-	Power Supply for LCD Drive
8	D0	H/L	Display Data
9	D1	H/L	Display Data
10	D2	H/L	Display Data
11	D3	H/L	Display Data
12	D4	H/L	Display Data
13	D5	H/L	Display Data
14	D6	H/L	Display Data
15	D7	H/L	Display Data
16	V _{SS}	-	Power Supply(OV,GND)

PIN ASSIGNMENT OF CCFL CONNECTION

Pin No.	SYMBOL	LEVEL	FUNCTION
1	HOT	-	Power Supply for CCFL(HOT)
2	NC	-	No Connection
3	NC	-	No Connection
4	GND	-	Power Supply for CFL(GND)

產品編號 LCBHBT161M		南亞塑膠工業股份有限公司	
NAME		DATE	
APPROVE		TITLE	
CHECK		DWG-NO	
DESIGN		CB-T161M Rev.A	
DRAW		MAY PING 87.05.20	
THIRD ANGLE PROJECT		UNIT : mm	
		SCALE :	